



MODELLO (Model)	PRESSIONE DI ESERCIZIO (Working press. range)	PORTATA (Flow Rate) l/min. a 5 bar	Ø D1	Ø D2	C mm	E mm	F mm	G mm	PESO (Weight) kg
FC - 2	3 ÷ 12	200	2"	3"	500	816	250	210	30
FC - 4	3 ÷ 12	400	2 1/2"	4"	500	816	265	210	30 / 36
FC - 8	3 ÷ 12	800	3"	6"	650	900	350	300	68 / 74
FC - 15		1500	4"	8"			380		
FC - 20	3 ÷ 12	2000	4"	8"	850	1216	370	380	95 / 116
FC - 25		2500		10"					

MATERIALI - MATERIALS

Corpo in acciaio al carbonio	Body: carbon steel
Flange: UNI/DIN PN16 o ANSI 150 - A105	Flanges: UNI/DIN PN16 o ANSI 150 - A105
Disco di rottura: vetro calibrato	Vapor seal device: calibrated glass
Ugello: acciaio INOX AISI 316	Nozzle: stainless steel AISI 316
Finitura: verniciatura epossidica/poliuretana RAL 3000	Finish: red epoxy/polyurethanic paint RAL 3000

A RICHIESTA - OPTIONAL

Corpo: acciaio INOX	Body material: stainless steel
Flange: acciaio INOX	Flanges material: stainless steel
Finitura: zincatura a caldo	Finish: hot dip galvanized