

UnQondo-Fomtec Mobile Foam Unit – MFT 125

Fomtec-UnQondo Mobile Foam Trolley is designed to provide foam solution to any risk area either for application of a foam blanket or fire fighting.

Then unit can be easily manoeuvred to any area without difficulty.

The tank can be recharged whilst in use and is Suitable for use with any brand of foam concentrate. The system can provide Foam delivery to any risk – Hydrocarbons or Polar solvents

Standard Features

Hose basket can be fitted for stowage of supply hose.

Rear castor wheels fitted with Parking Brake, this removing the parking stand. This makes manoeuvrability most simple and easy. The unit has perfect balance when both in Parked and in motion

Optional Items

Optional Medium Expansion Foam Branch can be used.

Larger Flow Inductor & Foam Branch 400 L / Min

Medium Expansion Foam Pourer for Spills etc

PVC Cover

Specification

▪ Trolley / Frame	Mild Steel – Powder Coated
▪ Wheels	2 x Solid rubber with Metal rim & 2 x Solid Rubber with swivel & Brake
▪ Tank	Glass fibre – 125 Litre with sight Glass
▪ Foam Branch	Low Expansion -200 L / Min – Stainless Steel
▪ Inductor	POK 200 L / Min -1 / 6% - Bypass Valve & Pick up Tube –Storz Coupling
▪ Hose	UnQondo Utility Hose Type 1 , 15 m x 38 mm with LA Couplings Fitted
▪ Flow	200 L / min @ 7 bar
▪ Range	15 M * @7 Bar
▪ Operating Time / Tank	20 Minutes @7 bar [Approx]
▪ Overall length	960 mm
▪ Overall Width	800 mm
▪ Mass Empty	55 Kg
▪ Stowage of hose	Provided in the Tank for flaked hose

* In still Air condition



Data Sheet : MFT 125	Mobile Foam Trolley
Ref : MFT 125 STD - 2006 / 05	
UnQondo Projects – Fire Protection Specialists Fomtec – Sweden- Fire Fighting Foams & Hardware	Unit 08 - Cranberry Industrial Park
Tel + 27 11 795 1688 / 795 1899 Fax + 27 11 795 1799 Email : admin@unqondo.co.za	Cranberry Street - Laser Park – Honeydew- Gauteng, S Africa