

UnQondo- Argus Utility Fire Hose
Classification: Type 1

UnQondo Argus Utility Fire Hose is an economical fire hose used mainly in industrial applications servicing Hydrant Hose Box stations. The hose is classified as a Type 1 Fire hose with a single yet strong adhesive lining of Poly Urethane. The lining provides good non percolating qualities and is also very pliable this making the hose very flexible and easy to handle. This also makes the hose easy to use when pressurised and does not kink under low pressure. Coiling for storage is also very easily done.
Colour: White

Couplings

Couplings can be fitted by means of the standard wire binding method. The couplings are either alight Alloy or gun metal materials. These are of the Double rib style and manufactured to BS 336. The castings are of high grade aluminium this maintain consistency in the wall thickness and trueness of the coupling



Key Features

- White Hose, pliable - easy to make up & use under low pressures with out kinking
- Washable after use
- Working Pressure – 16 Bar
- Strong adhesion between lining and jacket
- Light Alloy BIC Couplings or NST Couplings fitted

Size [Diameter] mm - inches	Test Pressure - Bar	Working Pressure - Bar	ID - mm	Weight [g/ m]	Length [m]
25 -1"	20	16	25	120	30
40 – 1.1/2"	20	16	38	160	30
50 – 2"	20	16	51	210	30
65 – 2.1/2 "	20	16	63.5	270	30

Data Sheet : Unqondo / Argus Utility Hose Type 1	Product : Utility Fire Hose
Ref : Unq/ARG T 1 Utility Hose	
UnQondo Projects – Fire Protection Specialists	
Tel + 27 11 795 1688 / 795 1899 Fax + 27 11 795 1799 Email : admin@unqondo.co.za	Unit 08 - Cranberry Industrial Park Cranberry Street - Laser Park – Honeydew- Gauteng, S Africa

KZN / E Cape: Argus Fire & General Engineering - Tel / Fax 031 264 1682: 082 444 7943