Unqondo Mobile Foam Trolley	
Model	MFT 125
Specification	
Hose Basket	Fitted to the Handle Bar, for stowage of 30 mm x 64 mm Layflat hose
Handle Bar	Mild steel tube 22 mm Dia, all bend to suit
Chassis & Frame	Angle iron, 25 mm, all welded together to accommodate Tank support bolts & base plate for Tank support
Wheels	2 each - 350 mm x 65 mm Solid Rubber wheels with 25 ID for axle
	2 each - 180 mm Swivel Wheels, with Locks
Axle	25 mm Solid Bar, fitted with retaining washers and split pins
Tank	125 Litre Capacity, Glass Fibre construction with internal re inforcement
	Filler Cap, 125 mm Plastic with coarse thread and retaining chain
	Pick Up Tube connector, 20 mm ID
	Level measuring by clear strip on side of tank, 1 side only
	Inductor Bolts [x 4] reinforced in the Tank
	Recess provided for stowage of 15 m x 45 mm Layflat Hose
Inductor	POK 200 L / 400 L / 800 L, with Bypass Valve and BIC Ends as standard
Foam Branch	Unqondo F 200 / F 400 / F 800 - S/Steel Low Expansion type [7:1] with BIC M inlet, Handle fitted for manouvering
Fire Hose	Optional - Unqondo Fire Flex, Type 3, 15 m x 38 mm - 1 each
	Optional - Unqondo Fire Flex, Type 3, 15 m x 64 mm - 1 each
Notes	